

# OTTOCOLL® S610

## + S-CA2030

### Sustainability data sheet

#### Inspections/authorisations



- French VOC-emission class A+

- Environmental Product Declarations (EPD)

Declaration number: EPD-DBC-20220179-IBF1-EN

#### Building certification system

##### QNG - Quality Seal for Sustainable Buildings

Version 1.3

<b>Criterion</b>	Avoiding harmful substances in building materials
<b>Overview table</b>	4. Adhesives and sealants - line 4.1
<b>Building product group</b>	Adhesives and sealants (acrylates and silicones) used on site indoors
<b>Requirements</b>	Product documentation and declaration of contained SVHC >0.1 % and chlorinated paraffins ≤0.1 % and declaration of biocidal active substances in silicones
<b>Classification</b>	<b>Meets the requirements, as declaration of contained SVHC &gt;0.1 % and chlorinated paraffins ≤0.1 % and declaration of biocidal active substances in silicones.</b>

##### DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2023

<b>Criterion</b>	ENV 1.2 Risks for the local environment	
<b>Criteria matrix</b>	line no. 13	
<b>Product type</b>	Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer, SMP, acrylate, silicone.	
<b>Requirements</b>	Quality category 1 (low)	<0.1 % halogenated propellant and bonus points SVHC ≤0.1 %
	Quality category 2	<0.1 % halogenated propellant and bonus points SVHC ≤0.1 %
	Quality category 3	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 <sup>PLUS</sup> or VOC <1 % and bonus points SVHC ≤0.1 %
	Quality category 4 (high)	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 <sup>PLUS</sup> or VOC <1 % and bonus points SVHC ≤0.1 %
<b>Classification</b>	<b>Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs + LCCPs) &lt;0.1 % and halogenated propellant &lt;0.1 % and VOC &lt;1 % und SVHC ≤0.1 %.</b>	

<b>Criterion</b>	ENV 1.2 Risks for the local environment
<b>Criteria matrix</b>	line no. 12
<b>Product type</b>	Sealants, sealant compounds, adhesives for punctiform and linear bonding of interior components and ventilation ducts within buildings. This refers to acrylate sealants/adhesives, silicone sealants and SMP (hybrid sealants).
<b>Requirements</b>	Quality category 1 (low) – Quality category 2 No chlorinated paraffins declared in the SDS Quality category 3 Chlorinated paraffins <0.1 % Quality category 4 (high) Chlorinated paraffins <0.1 %, solvents <1 % and PAH plasticisers <0.1 %
<b>Classification</b>	<b>Fulfills quality category 4 requirements with chlorinated paraffins &lt;0.1 %, solvents &lt;1 % and PAH plasticisers &lt;0.1 %.</b>

---

**BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)**

<b>Criterion</b>	1.1.6 Risks for the local environment
<b>Overview table</b>	6. Adhesives and sealants – line no. 8
<b>Construction product type</b>	Adhesives and sealants made of PU, SMP (silane-modified polymers), acrylate (including dispersion adhesives) or silicone for punctiform and linear bonding and sealing in the interior, including TGA.
<b>Requirements</b>	Quality category 1 (low) Documentation, declaration of contained SVHC >0.1 % and declaration of biocidal agents (if used). Quality category 2 Declaration of biocidal agents (if used) and declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: GISCODE PU10 or PU20 and TCEP <0.1 %. Quality category 3 Declaration of biocidal agents (if used) and declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: GISCODE PU10 or PU20 and TCEP <0.1 %. Quality category 4 No amine- or oxime-interlacing silicones. Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1 <sup>PLUS</sup> and chlorinated paraffins and declaration of biocidal agents (if used) and declaration of contained SVHC >0.1 %. For PU adhesives additionally applies: TCEP <0.1 %. Quality category 5 (high) No amine- or oxime-interlacing silicones. Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1 <sup>PLUS</sup> and chlorinated paraffins <0.1 % and declaration of biocidal agents (if used) and declaration of contained SVHC >0.1 %. For PU adhesives additionally applies: TCEP <0.1 %.
<b>Classification</b>	<b>Fulfills the quality category 3 requirements because of declaration of biocidal agents (if used) and declaration of contained SVHC &gt;0.1 % and chlorinated paraffins &lt;0.1 %.</b>
<b>Documentation documents</b>	All the listed documents can be downloaded from <a href="http://www.otto-chemie.com">www.otto-chemie.com</a> 1. Technical data sheet 2. Safety data sheet 3. Sustainability data sheet 4. Test certificates 5. Environmental product declaration

---

---

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: [www.otto-chemie.com](http://www.otto-chemie.com). Furthermore, the information in the documents accompanying the products is applicable.

---