OTTOSEAL® M 380

Sustainability data sheet

Inspections/authorisations



EMICODE[®] EC 1^{PLUS} – very low emission

ÉMISSIONS DANS L'AIR INTÉRIEUR'

French VOC-emission class A+

• Environmental Product Declarations (EPD)

Declaration number: EPD-FEI-20220021-IBG1-EN

Building certification system

QNG - Quality Seal for S	ustainable Buildings	
Version 1.3		
Criterion	Avoiding harmful substances in building materials	
Overview table	4. Adhesives and sealants - line 4.2	
Building product group	Adhesives and sealants processed on site based on PU, PU hybrid and SMP formulations (silane-modified polymers) in interior spaces	
Requirements	Product documentation and declaration of contained SVHC >0.1 % and chlorinated paraffins, TCEP, PBB and PBDs ≤0.1 % and solvent-free or GISCODE PU10, PU20, PU40 (ALT) or PU50 (ALT)	
Classification Meets the requirements, as declaration of contained SVHC > 0.1 % and chlorinate paraffins, TCEP, PBB und PBDE ≤ 0.1 % and solvent-free.		



DGNB – Deutsche G	esellschaft für Nachhaltiges B	auen (German Sustainable Building Council)		
Version 2023				
Criterion	ENV1.2 Risks for the local	ENV1.2 Risks for the local environment		
Criteria matrix	line no. 11			
Product type	Sealing compounds, sealants, adhesives for dot and line-formed bonding of building con on the interior: - mechanically stressed joints - baseboards - door rails - support adhesive (raised or hollow floor) - ventilation ducts			
	This refers to acrylic adhesives/bonding agents, silicone sealants, PU adhesives and silane- modified polymers (SMP).			
Requirements	Quality category 1 (low)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC \leq 0.1 %		
	Quality category 2	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC ≤0.1 %		
	Quality category 3	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE [®] EC 1^{PLUS} and bonus points SVHC $\leq 0.1 \%$		
	Quality category 4 (high)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE [®] EC 1^{PLUS} and bonus points SVHC $\leq 0.1 \%$		
Classification	Fulfills quality category 4 SVHC ≤0.1 %.	Fulfills quality category 4 requirements with GISCODE DH20 and EMICODE [®] EC 1 ^{PLUS} and SVHC ≤0.1 %.		
DGNB – Deutsche G	esellschaft für Nachhaltiges B	auen (German Sustainable Building Council)		
Version 2018				
Criterion	ENV1.2 Risks for the local environment			
Criteria matrix	line no. 12			
Product type	Sealants, sealant compounds, adhesives for punctiform and linear bonding of interior components and ventilation ducts within buildings. This refers to acrylate sealants/adhesives, silicone sealants and SMP (hybrid sealants).			
Requirements	Quality category 1 (low) Quality category 2 Quality category 3 Quality category 4 (high)	 No chlorinated paraffins declared in the SDS Chlorinated paraffins <0.1 % Chlorinated paraffins <0.1 %, solvents <1 % and PAH plasticisers <0.1 % 		
Classification		Fulfills quality category 4 requirements with chlorinated paraffins <0.1 %, solvents <1% and PAH plasticisers <0.1 %.		



stem Nachhaltiges Bauen (Ra	ating System for Sustainable Building)		
1.1.6 Risks for the local env	1.1.6 Risks for the local environment		
6. Adhesives and sealants – line no.8			
Adhesives and sealants made of PU, SMP (silane-modified polymers), acrylate (including dispersion adhesives) or silicone for punctiform and linear bonding and sealing in the interior, including TGA.			
Quality category 1 (low)	Documentation, declaration of contained SVHC > 0.1 % and declaration of biocidal agents (if used).		
Quality category 2	Declaration of biocidal agents (if used) and declaration of contained SVHC > 0.1% and chlorinated paraffins < 0.1%. For PU adhesives additionally applies: GISCODE PU10 or PU20 and TCEP < 0.1%.		
Quality category 3	Declaration of biocidal agents (if used) and declaration of contained SVHC > 0.1 % and chlorinated paraffins < 0.1 %. For PU adhesives additionally applies: GISCODE PU10 or PU20 and TCEP < 0.1 %.		
Quality category 4	No amine- or oxime-interlacing silicones. Additionally applies: RAL-UZ 123 or EMICODE [®] EC 1/EC 1 ^{PLUS} and chlorinated paraffins <0.1% and declaration of biocidal agents (if used) and declaration of contained SVHC >0.1%. For PU adhesives additionally applies: TCEP <0.1%.		
Quality category 5 (high)	No amine- or oxime-interlacing silicones. Additionally applies: RAL-UZ 123 or EMICODE [®] EC 1/EC 1 ^{PLUS} and chlorinated paraffins <0.1% and declaration of biocidal agents (if used) and declaration of contained SVHC >0.1%. For PU adhesives additionally applies: TCEP <0.1%.		
Fulfills the quality category 5 requirements as no amine- or oxime-interlacing silicone and EMICODE [®] EC 1 ^{PLUS} and declaration of biocidal agents (if used) and declaration of SVHC >0.1% and chlorinated paraffins <0.1%.			
All the listed documents can be downloaded from www.otto-chemie.com			
 Technical data sheet Safety data sheet Sustainability data sheet Test certificates Environmental product d 			
	 1.1.6 Risks for the local env. 6. Adhesives and sealants Adhesives and sealants madispersion adhesives) or sincluding TGA. Quality category 1 (low) Quality category 2 Quality category 3 Quality category 4 Quality category 5 (high) Fulfills the quality categor and EMICODE® EC 1^{PLUS} SVHC > 0.1% and chlorin All the listed documents cate 1. Technical data sheet 2. Safety data sheet 3. Sustainability data sheet 4. Test certificates 		

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.

