# OTTOSEAL® S94

Sustainability data sheet

## Inspections/authorisations



French VOC-emission class A+

### **Building certification system**

DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2015

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 12

**Product type** Sealants, adhesives for dot and line-formed bonding of building components on the interior

and the TGA (Technical Building Equipment). This refers to acrylate sealants/adhesives,

silicone sealants and SMP (hybrid sealants).

Requirements Quality category 1 (low) Chlorinated paraffins < 0.1 %

Quality category 2 Chlorinated paraffins < 0.1 % Chlorinated paraffins < 0.1 % Chlorinated paraffins < 0.1 %

Quality category 4 (high) Chlorinated paraffins < 0.1 %, solvents < 1 % and

PAH plasticisers < 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins <0.1%, solvents <1%

and PAH plasticisers < 0.1 %.

DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2015

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 13

**Product type** Adhesive for air tightness of facades inside and outside: e. g. PU, PU Hybrid, MS Polymer,

SMP or similar.

Requirements Quality category 1 (low) -

Quality category 2

Quality category 3 Chlorinated paraffins < 0.1 % and VOC < 1 % or

EMICODE® EC 1/EC 1 PLUS

Quality category 4 (high) Chlorinated paraffins < 0.1 % and VOC < 1 % or

EMICODE® EC 1/EC 1 PLUS

Classification Fulfills quality category 4 requirements with chlorinated paraffins < 0.1 % and

solvents < 1%.

Sustainability data sheet OTTOSEAL® S94

version: 1gb (17.10.2019 09:21 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com









#### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2015

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 42

Product type Technical fire protection, bonding or sealing in interiors, PU assembly adhesives: fireproofing

primers; fireproofing coatings for cables, fireproofing silicones, PU assembly adhesives for

insulating materials (EPS, XPS, PUR).

Requirements Quality category 1 (low) -

Quality category 2

Quality category 3 Chlorinated paraffins and TCEP < 0.1 % Quality category 4 (high) Chlorinated paraffins and TCEP < 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins and TCEP < 0.1 %.

#### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 12

**Product type**Sealants, sealant compounds, adhesives for punctiform and linear bonding of interior

components and ventilation ducts within buildings. This refers to acrylate sealants/adhesives,

silicone sealants and SMP (hybrid sealants).

Requirements Quality category 1 (low) -

Quality category 2 No chlorinated paraffins declared in the SDS

Quality category 3 Chlorinated paraffins < 0.1 %

Quality category 4 (high) Chlorinated paraffins < 0.1%, solvents < 1% and

PAH plasticisers < 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins <0.1 %, solvents <1 %

and PAH plasticisers < 0.1 %.

#### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 13

Product type Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer,

SMP or similar.

Requirements Quality category 1 (low) < 0.1 % halogenated propellant

Quality category 2 <0.1% halogenated propellant

Quality category 3 Chlorinated paraffins < 0.1 % and halogenated propellant < 0.1 %

and EMICODE® EC 1/EC 1 PLUS or VOC < 1 %

Quality category 4 (high) Chlorinated paraffins < 0.1 % and halogenated propellant < 0.1 %

and EMICODE® EC 1/EC 1 PLUS or VOC < 1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins < 0.1 % and

halogenated propellant < 0.1 % and VOC < 1 %.

Sustainability data sheet OTTOSEAL® S94 Page 2 version: 1gb (17.10.2019 09:21 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com









#### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 42

**Product type**Technical fire protection, bonding or sealing in interiors, PU assembly adhesives: fireproofing

primers; fireproofing coatings for cables, fireproofing silicones, PU assembly adhesives for

insulating materials (EPS, XPS, PUR).

Requirements Quality category 1 (low)

Quality category 2

Quality category 3 Chlorinated paraffins < 0.1 % and SVHC < 0.1 % Quality category 4 (high) Chlorinated paraffins < 0.1 % and SVHC < 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins < 0.1 % and

SVHC < 0.1%.

#### BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

**Criterion** 1.1.6 Risks for the local environment

Overview table 4. Surface coatings on predominantly non-mineral surfaces (wood, metals, plastics) – line no.44

Construction product type

Fire protection primers, fire protection coatings for cables, fire protection silicones for fillings, coatings, adhesives or sealings in interiors and exteriors with fire protection requirements.

**Requirements** Quality category 1 (low) Documentation and declaration of contained SVHC > 0.1 %.

Quality category 2 Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1 %.

Quality category 3 Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1%.

Quality category 4 Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1%.

Quality category 5 (high) Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1%.

Classification Fulfills the quality category 5 requirements as declaration of contained SVHC > 0.1 % and

chlorinated paraffins, PBB, PBDE, TCEP < 0.1%.

Sustainability data sheet OTTOSEAL® S94 Page 3 version: 1gb (17.10.2019 09:21 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de  $\cdot$  Internet: www.otto-chemie.com







#### BNB - Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

product type

Criterion 1.1.6 Risks for the local environment

Overview table 6. Adhesives and sealants – line no. 8

Construction

6. Adhesives and sealants – line no. 8

Construction

Adhesives and sealants made of PU. SMP (silane-modified polymers), acrylate (including

dispersion adhesives) or silicone for punctiform and linear bonding and sealing in the interior,

including TGA.

Requirements Quality category 1 (low) Documentation, declaration of contained SVHC > 0.1 % and

declaration of biocidal agents (if used).

Quality category 2 Declaration of biocidal agents (if used) and declaration of contained

SVHC > 0.1 % and chlorinated paraffins < 0.1 %.

For PU adhesives additionally applies: GISCODE PU10 or PU20

and TCEP < 0.1%.

Quality category 3 Declaration of biocidal agents (if used) and declaration of contained

SVHC > 0.1 % and chlorinated paraffins < 0.1 %.

For PU adhesives additionally applies: GISCODE PU10 or PU20

and TCEP < 0.1 %.

Quality category 4 No amine- or oxime-interlacing silicones.

Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1 PLUS and chlorinated paraffins and declaration of biocidal agents (if used)

and declaration of contained SVHC > 0.1 %.

For PU adhesives additionally applies: TCEP < 0.1 %.

Quality category 5 (high) No amine- or oxime-interlacing silicones.

Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1  $^{\rm PLUS}$  and chlorinated paraffins < 0.1 % and declaration of biocidal agents

(if used) and declaration of contained SVHC > 0.1 %. For PU adhesives additionally applies: TCEP < 0.1 %.

Classification Fulfills the quality category 3 requirements because of declaration of biocidal agents

(if used) and declaration of contained SVHC > 0.1 % and chlorinated paraffins < 0.1 %.

#### BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

Criterion 1.1.6 Risks for the local environment

Overview table 6. Adhesives and sealants – line no. 9

**Construction**Adhesives and sealants for the airtightness of facades inside and outside: e.g. PU, PU hybrid, MS polymer, SMP, etc. for punctiform and linear bonding of components for the airtightness of

facades, windows and external doors.

**Requirements** Quality category 1 (low) Documentation and declaration of contained SVHC > 0.1 %.

Quality category 2 Declaration of contained SVHC > 0.1 % and chlorinated

paraffins < 0.1 %.

For PU adhesives additionally applies: TCEP < 0.1%.

Quality category 3 Declaration of contained SVHC > 0.1 % and chlorinated

paraffins < 0.1 %.

For PU adhesives additionally applies: TCEP < 0.1 %.

Quality category 4 Declaration of contained SVHC > 0.1 % and chlorinated paraffins

<0.1 % and EMICODE® EC 1/EC 1 PLUS or VOC <10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.

Quality category 5 (high) Declaration of contained SVHC > 0.1 % and chlorinated paraffins

<0.1% and EMICODE® EC 1/EC 1 PLUS or VOC <10 g/l. For PU adhesives additionally applies: TCEP <0.1%.

For PO addressives additionally applies. TCEP < 0.1 %.

Fulfills the quality category 3 requirements as declaration of contained SVHC > 0.1 % and

chlorinated paraffins < 0.1 %.

Sustainability data sheet OTTOSEAL® S94 Page 4 version: 1gb (17.10.2019 09:21 h)

Classification

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com









# Documents for building certifications

All the listed documents can be downloaded from otto-chemie.de

- 1. Technical data sheet
- 2. Security data sheets
- 3. Sustainability data sheet
- 4. Inspection certificates

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.

Sustainability data sheet OTTOSEAL® S94 Page 5 version: 1gb (17.10.2019 09:21 h)









