

OTTO Cleaner C

The coating cleaner

Hydrocarbon-based cleaner

REC

Characteristics

- › Cleaning of substrate before adhesion
- › Very good cleaning and degreasing effect
- › Dries quickly leaving no residue
- › Ventilation time not required
- › Compatible with conventional powder coatings

Fields of application

- › Removing of dust, grease or oil films, residues of protection film, fresh PUR-foam and fresh sealant residues
- › Removing of fresh PU- and Epoxi-residues on surfaces and working equipment
- › Cleaning of aluminium profiles (plain, anodised aluminium or powder-coated)
- › For the cleaning of many surfaces in plastic and metal processing areas

Technical properties

Density at + 23 °C [g/cm³] ~ 0,7

Shelf life at 23 °C/50 % RH 24
[months]

These data are not suitable for the issue of specifications.
Please contact OTTO-CHEMIE before issuing specifications.

Important information

Cleaner C has shown to have very good compatibility with surfaces. Because of the variety of possible surface qualities (lacquerings, plastics etc.) applying customer tests is recommended. If colour pigments are being dissolved during the cleaning of powder-coated surfaces, this can indicate, that the curing of the powder coating was insufficient.

Application information

Apply the cleaner with a lint-free cotton cloth and remove the uncured adhesive.
Powder coated metallic profiles should always be cleaned in lengthwise direction (not rotating). Due to the large number of different powder coatings we cannot exclude that OTTO Cleaner F attacks very sensitive powder coatings. Residues of cured adhesives in the cotton cloths as well as frequent, strong and rotating cleaning facilitates the attack to powder coatings. For this reason we recommend to use always fresh cotton cloths for cleaning.
Due to the many possible influences during and after application, the customer always has to carry out trials first.
Please observe the recommended shelf life which is printed on the packaging.

Packaging

	1,000 ml aluminium bottle
<input type="radio"/> colourless	REC-55
Pieces per packaging unit	5



1,000 ml aluminium bottle

Pieces per pallet

Safety precautions

Please observe the material safety data sheet.

Disposal

Information about disposal: Please refer to the material safety data sheet.

Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at www.otto-chemie.de.