

OTTO Primer 1230

The primer for improving of the paintability of silicone sealants with paints and varnishes

PR 1230

Characteristics

- ▶ Primer to improve the paintability of silicone sealants with paints and varnishes
- ▶ Ventilation time not required

Technical properties

Density at + 23 °C [g/cm³] ~ 0,7
 Shelf life at 23 °C/50 % RH 12 [months]

These data are not suitable for the issue of specifications. Please contact OTTO-CHEMIE before issuing specifications.

Pretreatment

The adherent surfaces have to be clean, free from fat, dry and sustainable.

Important information

Due to the multitude of paint systems for wooden windows a general statement regarding adhesion properties or compatibility is not possible. Individual preliminary tests are required.

Application information

The sealant must be fully hardened before treatment with OTTO Primer 1230.

Apply primer thinly and evenly with a clean brush.

Please be aware that no contaminated brush is immersed into the primer in order to avoid interferences with the primer.

No drying time necessary

The period of time between the application of the primer and the continuation of application may be extended to several hours, if dust accumulation is avoided.

A second application of OTTO Primer 1230 can improve the adhesion and the progression of the paint.

Due to the many possible influences during and after application, the customer always has to carry out trials first.

Please observe the recommended shelf life which is printed on the packaging.

Packaging

	100 ml aluminium bottle	250 ml aluminium bottle
○ colourless	PR1230-50	PR1230-51
Pieces per packaging unit	15	15
Pieces per pallet		



Safety precautions

Please observe the material safety data sheet.

Hermann Otto GmbH
 Krankenhausstr. 14 | 83413 Fridolfing, Germany
 ☎ +49 8684 908-0 | @ info@otto-chemie.de
 www.otto-chemie.com

💡 Application advice
 ☎ +49 8684 908-4300
 @ tae@otto-chemie.de



Disposal

Information about disposal: Please refer to the material safety data sheet.

Warranty information

The above information and our technical application advice, whether verbal, in writing or by means of tests, are provided to the best of our knowledge, but are non-binding, including with regard to any third-party property rights. The information in this publication does not exempt the processor from carrying out their own tests on our products with regard to their suitability for the intended processes and purposes. The application, use and processing of our products and the products manufactured on the basis of our technical application advice are beyond our control and are therefore the sole responsibility of the processor. If the application for which our products are used is subject to an official authorisation requirement, the user is responsible for obtaining these authorisations. We reserve the right to adapt the product to technical progress and new developments. For the rest, we refer to our General Terms and Conditions, in particular with regard to any liability for defects. You can find our GTC at www.otto-chemie.de.